

# **the Companion**



Front View

## Internet Remote Control...in a 1 rack mount space

- **Plug & Play** to your Crown Broadcast transmitter
  - 15-pin DBA connector for transmitters pre-2007, full monitoring/limited control
  - 25-pin DBA connector for transmitters 2007+, full monitoring/full control
- But wait... **it will connect to any transmitter with an I/O port**
  - 15-pin DIN, full monitoring/limited control
  - 25-pin DIN, full monitoring/full control



Rear View

- Remote Metering/Control/Status function – 20+ can be programmed at once
- Silence monitoring and programmable alarms with e-mail alerts
- Three levels of Password Control
- Low power consumption for ultimate reliability
- Long-term logging of transmitter parameters
- Utilizes Opto-coupled control — no mechanical relays
- Easy path for future upgrades
- Use with your computer, tablet, cell phone, or all three

Users.....	Unlimited
Password Control Levels.....	3
“Virtual” Metering Channels (All can be renamed).....	20
Relays (Each can be defined as either Pulse or Toggle).....	9
DB Connectors.....	15 or 25
Opto-Coupled Control.....	12 volt maximum
Chassis Dimensions .....	7 x 16.5 x 1 inches (17.8 x 41.9 x 44.5 cm)
Chassis .....	1RU
Weight .....	4 lbs
Logging of input status .....	1/hour to 1/day
External Temperature probe.....	Included
Stereo Silence Sensor monitoring.....	Enabled
Front Panel.....	LED indicator
Rear Panel.....	RJ-45, 10/100base-T LAN/Ethernet interface
Warranty.....	5-Year

2524 Toledo Rd, Elkhart, IN 46516 574-262-8900

